

Turbo Disc segment selector



Subfloor	 Grit 20 Medium floor Art. # 105530 (4 pcs.)	 Grit 20 Soft floor Art. # 105660 (4 pcs.)	 Grit 70 Medium floor Art. # 105540 (4 pcs.)	 Grit 70 Soft floor Art. # 105670 (4 pcs.)	 Grit 120 Art. # 105550 (4 pcs.)	 PCD Split Art. # 105680 (4 pcs.)
Hard concrete or similar	✓					
Soft concrete or similar		✓				
Screed, only the "tops"			✓			
Screed, renovation	✓					
Soft concrete, fine sanding				✓		
Extra fine sanding					✓	
Mastic asphalt		✓				
Epoxy, thin layer	✓					
Polyurethane						✓
Paint, tough						✓
Glue thin < 1 mm						✓
Cardboard	✓					
Jute/Action back						✓

✓ **Best choice**



Watch out for bolts and screws!

Please remove all foreign objects from the floor before sanding.
The segments can be destroyed running over metal.




Hard or soft surface?

Please perform a scratch test to determine if you should use segments for hard or soft concrete (or similar) or segments for epoxy or tough paint.



Have you chosen the right segments for the job?

Please monitor the wear of the segments closely.
For the first time after approximately half an hour.
Change the segments if the wear is unusually.



Want to remove thick layers of material?

Thick layers of glue (> 1 mm), carpet backside, tile mortar etc. are easily removed using our iDISC mounted with PCDxtreme segments.