




















## 56 CM KLINGER TIL FUGEFRIE GULVE

## Klingeguide

Alle klinger sælges i pakker med 10 stk.

Varenr. (DB.nr.)	Tand-Profil	Udlagt materiale		Dimensioner [mm]				
		Tykkelse* [mm]	Forbrug** [kg/m <sup>2</sup> ]	Tandbredde (A)	Hul-bredde (B)	Tand-højde (C)	Vinkel (D)	
-	-	-	-	-	-	-	-	
101560	Glat	-	-	-	-	-	-	
101400	A1	0,41	0,41 - 0,58	0,5	1,5	1,1	55°	
101340	A2	0,4	0,40 - 0,56	1,3	1,7	1,4	55°	
101410	A3	0,6	0,60 - 0,84	0,4	1,6	1,5	45°	
101420	A4	0,28	0,28 - 0,39	0,4	1,1	0,75	55°	
101430	A5	0,24	0,24 - 0,34	1,45	1,35	1	55°	
101350	B1	0,48	0,48 - 0,67	2,6	2,4	2	55°	
101440	B2	0,77	0,77 - 1,07	2	3	2,55	55°	
101450	B3	0,86	0,86 - 1,20	3,3	3,7	3,25	55°	
101530	B5	0,73	0,73 - 1,02	14,30	5,70	5,15	55°	
101460	S1	1,21	1,21 - 1,69	0,1	1,8	2,55	30°	
101470	S2	1,64	1,64 - 2,29	0,1	4,2	3,35	60°	
101700	3x3	1,2	1,20 - 1,67	0,1	2,4	2,5	55°	
101690	4x4	1,55	1,55 - 2,16	0,1	3,4	3,2	55°	
101650	5x5	1,71	1,71 - 2,38	0,1	4,4	3,5	55°	
101710	6x6	2,6	2,60 - 3,61	0,1	5,7	5,3	55°	
101360 1744960	R1	2,18	2,18 - 3,05	1,5	4	3	0°	 R1
101370 1744961	R2	3,33	3,33 - 4,67	2	4	5	0°	 R2
101660 1744963	R3	3,11	3,11-4,35	2,4	6	5	U	 R3

\*) Lagtykkelsen kan forøges med op til 40% afhængigt af underlaget

\*\*) Vægten er angivet uden tilsætningsmateriale

 Klinger til komponentprodukter Klinger til komponentprodukter og flydespartel